

300V PVC 花線(VCTF)



- 規格：依據 CNS 3199
- 用途：低壓電器及室內用
- 額定：300V 以下
- 構造：導體- 圓形軟銅絞線
絕緣- PVC
被覆- PVC
- 識別：4C 以下以絕緣顏色識別(黑、白、紅、綠)
5C 以上為黑色絕緣印白色線號 NO.1-NO.XX(指定芯數)
- 備註：PVC 被覆體具有抗 UV (Sunlight Resistance)功能。
電纜材料符合 RoHS 特性。

標稱截面積 mm ² xC	導體		絕緣體厚度 mm	被覆體厚度 mm	完成外徑 (約) mm	最大導體電阻 (20℃) Ω/km	交流耐電壓 (A.C.) (水中) (空中)		最小絕緣電阻 (20℃) (60℃)		火花試驗 kV/Sec										
	組成 No./mm	外徑 (約) mm					kV/分		MΩ-km												
0.5 x 2	20/0.18	0.9	0.6	1.0	6.1	37.8	1/1	3/1	5	0.01	5/0.15										
0.5 x 3					6.5																
0.5 x 4					7.0																
0.5 x 5					7.7																
0.5 x 6					8.3																
0.5 x 7					8.3																
0.5 x 8					9.0																
0.5 x 10					10.4																
0.5 x 12					10.8																
0.5 x 16					11.9																
0.5 x 20					13.2																
0.5 x 24					14.6																
0.5 x 30					15.5																
0.75 x 2					30/0.18							1.1	0.6	1.0	6.5	25.1	1/1	3/1	5	0.01	5/0.15
0.75 x 3															6.9						
0.75 x 4	7.5																				
0.75 x 5	8.3																				
0.75 x 6	8.9																				
0.75 x 7	8.9																				
0.75 x 8	9.7																				
0.75 x 10	11.2																				
0.75 x 12	11.6																				
0.75 x 16	12.9																				
0.75 x 20	14.3																				
0.75 x 24	15.8																				
0.75 x 30	16.8																				
1.25 x 2	50/0.18	1.5	0.6	1.0		7.3	15.1	1/1	3/1	5	0.01				5/0.15						
1.25 x 3						7.8															
1.25 x 4					8.5																
1.25 x 5					9.3																
1.25 x 6					10.1																
1.25 x 7					10.1																
1.25 x 8					11.0																
1.25 x 10					12.8																
1.25 x 12					13.3																
1.25 x 16					14.7																
1.25 x 20					16.4																
1.25 x 24					18.3																
1.25 x 30					19.5																
2 x 2					37/0.26	1.8						0.6	1.0	7.9		9.79	1/1	3/1	5	0.01	5/0.15
2 x 3														8.4							
2 x 4	9.2																				
2 x 5	10.1																				
2 x 6	11.0																				
2 x 7	11.0																				
2 x 8	12.0																				
2 x 10	14.0																				
2 x 12	14.5																				
2 x 16	16.1																				
2 x 20	18.1																				
2 x 24	20.1																				
2 x 30	21.4																				

* 版權屬於華新麗華股份有限公司所有，非經授權不得擅自修改或複製。



總公司：台北市信義區松智路 1 號 25 樓
新莊廠：新北市新莊區新樹路 397 號

TEL：(02) 87262211
業務專線 TEL：(02) 22029121
FAX：(02) 22025166

FAX：(02) 27202234
TEL：(02) 22025155